

What is claimed is:

1. An umbrella handle adapted for hanging to a closed
item, comprising a handle coaxially connected to
5 a central shaft to form an umbrella, a handle strap
being secured at an inner end to said handle, and
a clip hooking means provided at a predetermined
position on an outer surface of an extension wall
of said handle;
10
whereby by extending an outer section of said handle
strap through a closed item and turning said handle
strap to engage said outer section of said handle
strap with said clip hooking means, said umbrella
15 is hung to said closed item.
2. The umbrella handle adapted for hanging to a closed
item as claimed in claim 1, wherein said clip hooking
means comprises a hook.
- 20
3. The umbrella handle adapted for hanging to a closed
item as claimed in claim 2, wherein said hook is
integrally formed on said handle.
- 25 4. The umbrella handle adapted for hanging to a closed

item as claimed in claim 2, wherein said hook is separately formed and then secured to said handle by means of a fastening element.

5 5. The umbrella handle adapted for hanging to a closed item as claimed in claim 4, wherein said fastening element comprises a screw.

6. The umbrella handle adapted for hanging to a closed
10 item as claimed in claim 2, wherein said handle strap is a loop-shaped strap, said outer section of said handle strap forms a turning point on said loop-shaped strap, and said handle strap is engaged with said clip hooking means at said turning point.

15

7. The umbrella handle adapted for hanging to a closed item as claimed in claim 2, wherein said handle strap is provided on said outer section with an annular ring member adapted to engage with said
20 hook.

8. The umbrella handle adapted for hanging to a closed item as claimed in claim 1, wherein said clip hooking means comprises a locating groove having an open
25 top, a width of which is narrowed to be equal to

or slightly smaller than a diameter of said handle
strap, and said handle strap is provided at said
outer section with a ball head, which is adapted
to insert in and thereby retained to said locating
5 groove.